



GENESIS SERIES

**Low Voltage Cable
Part No. 3320**

Description: 22 AWG 1PR Shielded Low Cap CMP-CL3P
 Specifications: UL Standards 13 & 444; NEC Articles 725 & 800; EIA/TIA 485

Construction:

Conductor 22 AWG 7/.0096 Stranded Bare Copper
 Insulation Foam FEP
 Insulation Thickness 0.018" nom.
 Insulation Colors Black, White
 Insulation Diameter 0.065 nom.
 Lay Length 2.0" nom. - LHL
 Drain Wire 24 AWG 7/32 Tinned Copper
 Shield 0.001" Thick Aluminum/Mylar – 100% coverage

Jacket Plenum PVC
 Ripcord Yes
 Color Raspberry, Orange, Green, Blue
 Jacket Thickness 0.015" nom.
 Outside Diameter 0.165" nom.

Legend (Ink Print)

HONEYWELL P/N 3320 1PR22 SHIELDED LOW CAP EIA/TIA 485 E175106 (UL) CL3P OR
 CMP C(UL)US 75C FT6 (ROHS) W/O# XXXXXX-XXXXXX XXXXX FT DEVICE/ZONE A B C
 D E F 1 2 3 4 5 6 7 8 9

Packaging 1000 ft reel or reel-in-a box

Properties

Temperature Rating -20 to 75°C
 Operating Voltage 300 Volts max.
 Capacitance 12.5 pf/ft nom.
 Impedance 115 ± 5 Ohms
 DC Resistance 15 Ohms/M' at 20°C
 Flame Rating NFPA 262, CSA FT6