



386 Internationale Drive Suite H, Bolingbrook, Illinois 60440
 Tel: (708) 493-1191 Toll Free: (800) 379-1191 Fax: (630) 296-8100


Temperature Control SmartWire™

UL Listed and Rated Type CL3P or CMP
 Multi-Conductor Non-Shielded Plenum Cable

P/N 002370 - 18 AWG 3 Conductor Non-Shielded Plenum



Cable Specifications	
Description:	18 AWG 3 Conductor Bare Copper, Non-Shielded Plenum, UL Subject 444, Type CL3P/CMP, (UL)
Conductor Description:	18 (7/26 Bare Copper)
Insulation:	Low-Smoke PVC .009"
Color Code:	Black/White/Red
Jacket:	Low-Smoke PVC .170"
Marking:	TEMPERATURE CONTROL SYSTEM AN BIN DIG IN / OUT A B C D E 0 1 2 3 4 5 6 7 8 9 18AWG (UL) CL3P CMP RoHS
Overall Diameter:	.175" Nom.
Conductor DCR:	N/A
Capacitance:	N/A
Impedance:	N/A
Temperature and Voltage Rating:	60 C / 300 Volt
Cable Weight:	23 Lbs/Mft.



Flame Rating:

Approved For Plenum Use Without Conduit Per NEC Article 800 by Passing UL-910 Steiner Tunnel Test

Agencies Approvals:

NEC Article 800, 725; UL CL3P/CMP, C(UL), RoHs Compliant

