



386 Internationale Drive Suite H, Bolingbrook, Illinois 60440
 Tel: (630) 633-4500 Toll Free: (800) 379-1191 Fax: (630) 296-8100

**UL Listed and Rated Type CMP
 Plenum Composite Cable**

P/N **NOVCOMBO** - Element 1: 20 AWG 2 Conductor Shielded;
 Element 2: 18 AWG 1 Pair Non-Shielded Plenum Composite Cable

Cable Specifications	
Description:	Element 1: 20 AWG 2 Conductor Bare Copper Shielded; Element 2: 18 AWG 2 Conductor Bare Copper Non-Shielded, Plenum Composite Cable UL Type CMP, C(UL)
Conductor Description:	Element 1: 20 AWG 7 Strand Bare Copper; Element 2: 18 AWG 7 Strand Bare Copper
Insulation:	Both Elements: Low-Smoke PVC .008"
Color Code:	Element 1: Black/Red; Element 2: White/Green
Shield:	Element 1: Aluminum Mylar; Element 2: N/A
Drain Wire:	Element 1: 24 AWG 7 Strand Tinned Copper; Element 2: N/A
Jacket:	Outer Jacket: Low-Smoke PVC .018"
Marking:	NOVAR CONTROLS 709022000 A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG 2C UNS + 20 AWG 2C OAS UL C(UL) CMP ROHS MADE IN THE USA
Overall Diameter:	.191" Nom.
Conductor DCR:	N/A
Capacitance:	N/A
Impedance:	N/A
Velocity of Propagation:	N/A
Temperature & Voltage Rating:	75 C / 300 Volt
Cable Weight:	.

Flame Rating:

Approved For Plenum Use Without Conduit Per NEC Article 800 by Passing UL-910 Steiner Tunnel Test

Agencies Approvals:

UL Listed Type CMP, C(UL), RoHS Compliant, Made in the USA

