

HONEYWELL
Customer Specification

Part Number: 34111001N
Description: 18 AWG 2/C Str OAS CMP-CL2P
Specifications: UL Standards 13 & 444; NEC Articles 725 & 800

Construction:

Conductor 18 AWG 7/26 Stranded Bare Copper
Insulation Plenum PVC
Insulation Thickness 0.007" nom.
Insulation Colors **Black, White**
Insulation Diameter 0.007" nom.
Lay Length 2.25" nom.
Drain Wire 22 7/30 TC
Shield 0.001" Thick Aluminum/Mylar

Jacket Plenum PVC
Color **White**
Jacket Thickness 0.015" nom.
Outside Diameter 0.154" nom.
Legend (Ink Print)

**NOVAR BUILDING MANAGEMENT 18 AWG 2/C (UL) CMP-CL2P E175106 (RoHS) W/O#
XXXXXX-XXX C(ETL) FT6 XXXXX FT 60C 300V**

Packaging 1000' Reels (# 504WD)

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 60 pf/ft nom.
Impedance 34 Ohms nom.
DC Resistance 6.5 Ohms/M' at 20°C
Flame Rating UL910, CSA FT6

Customer Signature _____

Date _____